

# Agilent E9850A

## VXI Embedded PC Controller, 450 MHz

### Data Sheet

- 2-Slot, C-size, message based
- 450 MHz Intel Pentium® II Processor
- VXI*plug&play* compatible with Windows NT 4.0
- VISA and SICL support
- 64 MB standard SDRAM memory



Agilent E9850A

## Description

The Agilent Technologies E9850A is a **C-size, 2-slot, message-based VXI embedded PC controller running Win NT 4.0 operating system**. The E9850A can be embedded in various Agilent VXI mainframes including the E84XX series, E1401B or E1421B.

The E9850A 450 MHz Pentium II uses Intel "Slot 1" architecture that allows the processor to be upgraded in the field. Standard features include a 4.2 GB Ultra DMA 33 hard drive/disk, a 3.5-inch 1.44 MB floppy drive, and 64 MB RAM standard memory that can be expanded to 192 MB using standard SODIMMs in two free sockets.

Standard features include an internal AT/PCI expansion slot that accepts a full-length PCI card, or a 16-bit XT-height ISA bus card. In addition, two front panel slots can accept one Type I/II/III and one Type I/II PC card (PCMCIA) peripherals.

Several standard I/O ports include an Advanced Graphics Port (AGP), a 2 MB 64-bit accelerated SGRAM port for SVGA connection, a Wide Ultra SCSI-3 port, a 10/100 BaseT (RJ45) Ethernet port, an IEEE 488.2 GPIB port, two RS-232 serial ports, an IEEE-1284-compatible parallel port, and two USB ports. (Note: USB not supported in Win NT 4.0.) A PS/2 keyboard, keyboard adapter and PS/2 mouse are also standard.

Refer to the Agilent Technologies Website for instrument driver availability and downloading instructions, as well as for recent product updates, if applicable.

**Note:** The Agilent E9850A includes a 2.5-inch hard drive designed for relatively low-usage notebook PC applications. For applications requiring more than one disk read/write per minute over continuous long periods, premature hard drive failure may occur. For such applications, consider using an external SCSI hard drive.



**Agilent Technologies**  
Innovating the HP Way

## Product Specifications

<b>Processor:</b>	Intel Pentium® II
<b>Clock speed:</b>	450 MHz
<b>O.S. (earliest supported):</b>	Windows NT 4.0
<b>Internal mass storage:</b>	4.2 GB Hard Drive
	3.5-in. Floppy Drive (see Note below)
<b>Main memory:</b>	64 MB standard expandable to 192 MB using SODIMMS
<b>Available internal slot:</b>	Accepts full-length PCI or 16-bit XT-height ISA card
<b>Available front panel slots:</b>	Two PC card (PCMCIA) slots that accept one Type I/II/III and one Type I/II cards
<b>Standard built-in interfaces:</b>	Wide Ultra SCSI-3 port (AGP) 2 MB 64-bit accelerated SGRAM SVGA port 10/100 BaseT Ethernet port IEEE 488.2 GPIB port Two RS-232 serial ports IEEE-1284 parallel port Two USB ports* * (not supported in Win NT 4.0)
<b>Included cables:</b>	GPIB cable RS-232 cable IEEE-1284-2 cable (printer) PS-2 keyboard adapter (DIN 5F/MINI 6M)

### Advanced Graphics Port (some of the supported resolutions):

Resolution	Number of colors
640 x 460	16 M colors
800 x 600	16 M colors
1024 x 768	64 K colors
1280 x 1024	256 colors
1600 x 1200	256 colors

<b>Additional front panel connectors/functions:</b>	10 MHz Clock I/O SMB connector Trigger-In SMB connector Trigger-Out SMB connector Audio Out (speaker) connector Keyboard connector Mouse connector
---	---

### Front panel LEDs:

#### VXIbus interface status LEDs (indicate initial-ization stages as PC boots):

FAIL
SYSF
ONLINE
PWROK

#### Board access LEDs (indicate that board resources have been accessed):

ACC
DRV
SCSI

#### Ethernet LEDs (indicate Ethernet interface status):

RX/TX
LNK
100B-T

**Note:** Processor, RAM and hard disk technologies are improving rapidly, so the Agilent E9850A processor, RAM and hard disk may be upgraded without notice.

## Environmental Specifications

<b>EMC specifications:</b>	Meets CISPR 11, 1990/EN 55011 (1991): Group 1, Class A
<b>EMI specifications:</b>	FCC Class A verified
<b>Functional shock:</b>	MIL-T-28800E Class 3 (30 g peak, half sine shock pulse). Also meets IEC 60068-2-27.
<b>Random vibration:</b>	MIL-T-28800E MIL-STD-810E Category 1
<b>Operating:</b>	5 to 500 Hz, 0.3 grms, 3-axes
<b>Non-operating:</b>	5 to 500 Hz, 2.4 grms, 3-axes
<b>Operating environment:</b>	
<b>Ambient temperature:</b>	0 to 50 °C
<b>Relative humidity:</b>	10% to 90% non-condensing
<b>Storage environment:</b>	
<b>Ambient temperature:</b>	-20 to + 70 °C
<b>Relative humidity:</b>	5% to 95% non-condensing
<b>Maximum altitude:</b>	
<b>Operating:</b>	10,000 ft
<b>Non-operating:</b>	40,000 ft

## General Specifications

### General Characteristics

Dimensions:	233.4 mm high x 340 mm deep (9.2 in. x 13.4 in.)
Weight:	2.5 Kg (5.5 lbs.)
VXI slots required:	2

### VXI Characteristics

VXI device type:	Message based
Size:	C
Slots:	2
Connectors:	P1/P2
VXI busses:	TTL Trigger Bus ECL Trigger Bus
C-size compatibility:	n/a

### Cooling/Slot

Watts/slot:	24/slot (48/2-slots)
$\Delta P$ mm H <sub>2</sub> O:	0.07
Air flow liter/s:	1.9

### Module Current

	I <sub>PM</sub>	I <sub>DM</sub>
+5 V:	9.0 A	4.0 A
+12 V:	70 mA	30 mA
-12 V:	10 mA	10 mA
+24 V:	1 mA	1 mA
-24 V:	1 mA	1 mA
-5.2 V:	350 mA	30 mA
-2 V:	100 mA	6 mA

### Ordering Information

Description	Product No.
VXI Embedded PC Controller, 450 MHz (includes operating manuals)	E9850A**
** Standard warranty is one year return-to-Agilent.	

## Related Literature

*2000 Test System and VXI Catalog CD-ROM*,  
Agilent Pub. No. 5980-0308E (detailed specifications for VXI products)

*2000 Test System and VXI Catalog*,  
Agilent Pub. No. 5980-0307E (overview of VXI products)

*1998 Test System and VXI Products Data Book*,  
Agilent Pub. No. 5966-2812E

## Online

Internet access for Agilent product information, services and support  
[www.agilent.com/find/tmdir](http://www.agilent.com/find/tmdir)

VXI product information  
[www.agilent.com/find/vxi](http://www.agilent.com/find/vxi)

Defense Electronics Applications  
[www.agilent.com/find/defense\\_ATE](http://www.agilent.com/find/defense_ATE)

Agilent Technologies VXI Channel Partners  
[www.agilent.com/find/vxichanpart](http://www.agilent.com/find/vxichanpart)

Agilent Technologies' HP VEE Application Website  
[www.agilent.com/find/vee](http://www.agilent.com/find/vee)

Agilent Technologies Data Acquisition and Control Website  
[www.agilent.com/find/data\\_acq](http://www.agilent.com/find/data_acq)

Agilent Technologies Instrument Driver Downloads  
[www.agilent.com/find/inst\\_drivers](http://www.agilent.com/find/inst_drivers)

Agilent Technologies Electronics Manufacturing Test Solutions  
[www.agilent.com/go/manufacturing](http://www.agilent.com/go/manufacturing)

**Get assistance with all your test and measurement needs at  
[www.agilent.com/find/assist](http://www.agilent.com/find/assist)**

**or check your local phone book for the Agilent office  
near you.**

## Agilent Technologies' test and measurement service/support commitment

Agilent strives to maximize the value our test and measurement products give you, while minimizing your risk and service/support problems. We work to ensure that each product is realistically described in the literature, meets its stated performance and functionality, has a clearly stated global warranty, and is supported at least five years beyond its production life. Our extensive self-help tools include many online resources ([www.agilent.com](http://www.agilent.com)).

Experienced Agilent test engineers throughout the world offer practical recommendations for product evaluation and selection. After you purchase an Agilent product, they can provide no-charge assistance with operation verification and basic measurement setups for advertised capabilities. To enhance the features, performance, and flexibility of your test and measurement products—and to help you solve application challenges—Agilent offers free or extra-cost product options and upgrades, and sell expert engineering, calibration, and other consulting services.

### Phone and fax

United States:  
Agilent Technologies  
(tel) 1 800 452 4844

Canada:  
Agilent Technologies Canada Inc.  
(tel) 1 877 894 4414

Europe:  
Agilent Technologies  
Test & Measurement  
European Marketing Organisation  
(tel) (31 20) 547 2000

Japan:  
Agilent Technologies Japan Ltd.  
(tel) (81) 426 56 7832  
(fax) (81) 426 56 7840

Latin America:  
Agilent Technologies  
Latin American Region Headquarters, U.S.A.  
(tel) (305) 267 4245  
(fax) (305) 267 4286

Australia/New Zealand:  
Agilent Technologies Australia Pty Ltd.  
(tel) 1 800 629 485 (Australia)  
(fax) (61 3) 9272 0749  
(tel) 0 800 738 378 (New Zealand)  
(fax) (64 4) 802 6881

Asia Pacific:  
Agilent Technologies, Hong Kong  
(tel) (852) 3197-7777  
(fax) (852) 2506-9284

Data Subject to Change  
© Agilent Technologies 2000  
Printed in the U.S.A. 04/2000  
Publication No.: 5980-0285E



**Agilent Technologies**  
Innovating the HP Way