

# 3 Steps to Better Baseband, IF and RF Design with the HP 8751A

## Application Brief AN 1202-3

**HP 8751A  
Network Analyzer  
5 Hz to 500 MHz**

**Summary:** This note details how to improve product design and testing with the enhanced measurement capabilities of the HP 8751A.

### Step 1



#### Start with Measurement Performance

Greater measurement accuracy results in increased design confidence and design success. The 1 mHz frequency resolution of the HP 8751A allows testing of even the most demanding narrow-band, high-Q, devices.

Measurement uncertainty is reduced because system performance characteristics are given not only for the HP 8751A network analyzer itself, but also together with the S-parameter test set, HP 87511A. Join this capability with calibration menu choices up to full 2-port, which effectively removes all 12 correctable system errors, and you get accurate and reliable results.


#### The Right Answers—the First Time

Traditional network analyzers often have frequency discrepancies depending on the sweep direction and sweep speed. The HP 8751A solves this problem with its digital pre-tuning technique which reduces frequency uncertainty.



With the HP 8751A you don't trade performance for speed. Resolution bandwidths, from 2 Hz to 4 kHz, allow you to tune and test in real-time. For example, a 201 point sweep updates as fast as 11 times per second. The 4-trace, color display puts more information at your disposal.

In addition to the pre-tuning technique and sweep update rates, the advanced list sweep function is also optimized to give you maximum performance in minimum time.



**Figure 1.**  
The HP 8751A gives you fast list sweeps with 130 dB dynamic range.

Frequency, power, IF bandwidth and number of points (up to 801 points), can be set for each individual sweep segment. Figure 1, above, shows how power can be varied from segment to segment, (lower trace) to extend the dynamic range to 130 dB (upper trace). Complete control of these list sweeps is another tool you can use to test devices more thoroughly and in less time.


## Step 2

### Document Your Success

If your job is not complete until the paperwork is done, then you will really appreciate the HP 8751A. Documentation of results, an important task of every engineer, is quick and easy.

Save test set-ups and results to disk in either HP's LIF or MS-DOS® formats with the built-in disk drive. You can then link data to many popular software packages on workstations or personal computers.

Transfer test results from the HP 8751A directly into desktop-published reports. For example, the graph in the test report shown below, in figure 2, was saved on the HP 8751A in HP's Graphics Language format (HP-GL), while the table of values was saved as an ASCII table and then exported to Lotus 1-2-3®. These files were then imported into Microsoft® Word to generate the report.



**Figure 2.**  
Complete test reports like this are easy with the HP 8751A and your PC.


## From Test . . . to Test Report . . . to Automatic Test Station

Print or plot hard-copies directly, complete with a time-stamp, with the HP 8751A. Or, save to disk for later printing. Figure 3 shows a record of operating parameters.

| OPERATING PARAMETER  | Channel 1 | Channel 2  |
|----------------------|-----------|------------|
| NUMBER of POINTS     | 51        | 800        |
| SWEPT TIME           | 2.783 s   | 320.4 s    |
| SOURCE POWER         | 10 dBm    | -5 dBm     |
| PORT 1 ATTEN.        | 0 dB      | 0 dB       |
| PORT 2 ATTEN.        | 0 dB      | 0 dB       |
| INPUT A ATTEN.       | 20 dB     | 20 dB      |
| INPUT B ATTEN.       | 20 dB     | 20 dB      |
| INPUT C ATTEN.       | 0 dB      | 0 dB       |
| IF BANDWIDTH         | 20 Hz     | 1 kHz      |
| AVERAGING FACTOR     | 1         | 16         |
|                      | OFF       | ON         |
| SMOOTHING APERTURE   | 1 X SPAN  | 5 X SPAN   |
|                      | OFF       | ON         |
| GROUP DELAY APERTURE | 1 X SPAN  | 1 X SPAN   |
| CAL KIT              | 7m        | 7m         |
| Z0                   | 50        | 50         |
| CAL TYPE             | RESPONSE  | S11 1-PORT |

**Figure 3.**  
Complete test records at the touch of a button.

If you use markers to measure key parameters, then you will benefit from the marker page display, which can be hard-copied directly to a printer. Figure 4 shows how this feature is used with a measurement of a filter.



**Figure 4.**  
Key parameters are easy to measure and document with the marker page function.


### Step 3

#### **Automate Easily with HP IBASIC**

Get added flexibility and performance by putting a computer right inside the HP 8751A with Option 002, HP Instrument BASIC. Save time by automating repetitive or complex tasks such as device characterizations. Control other test equipment and peripherals via HP-IB and the digital I/O port.

Since HP IBASIC puts an instrument controller right inside the HP 8751A, configuring a stand-alone test station costs less and is simpler with Hewlett-Packard providing a one-vendor solution.

Reduce complex tests to one-button measurements with HP IBASIC. Use the built-in keystroke recording function to sequence operation of the HP 8751A to fit your test procedure. Similar to the macro recording found in many PC



**Figure 5.**  
HP 8751A with opt 002, HP IBASIC, controlling a test station.

programs, this function simplifies program generation by capturing manual keystrokes into an HP IBASIC program. Then access your new function from the front-panel softkey menu using any title or label you choose.

For example, you can completely automate complicated tests such as power sweep at different frequencies using several IF bandwidths over temperature or time. HP IBASIC adds extra capabilities that allow custom interfaces to be designed for each user, and ease the transition from design lab to manufacturing floor.

Programs developed with HP IBASIC can be used not only for initial development work in the lab but also can be given to the manufacturing engineer to form the basis of a production test program.

To further automate filter and resonator measurements, use the built-in Waveform Analysis commands of the HP 8751A. These commands, accessible via HP-IB or with HP IBASIC, return measured values of key parameters of filters and resonators by invoking a single command. Replace time-consuming manual marker manipulations with these Waveform Analysis commands.

For more information on the HP 8751A, including HP IBASIC, please see the referenced documents.

Also ask for:

*HP 8751A Network  
Analyzer Brochure*  
(part number: 5952-2370)

*HP 8751A Technical Data Sheet*  
(part number: 5952-2373)

*HP Instrument Basic  
HP 8751A Option 002  
Technical Data Sheet*  
(part number: 5091-2034E)

*HP 8751A Ordering Guide*  
(part number: 5952-2372)

*Designing Impedance Matching  
Networks with the HP 8751A  
Application Note 1202-1*  
(part number: 5091-1560E)

*17 Fixtures, Test Sets and  
Accessories for the HP 8751A  
Application Brief AN 1202-2*  
(part number: 5091-1985E)

HP-IB is Hewlett-Packard's implementation of IEEE Standard 488-1978

Lotus and 1-2-3 are U.S. registered trademarks of Lotus Development Corporation

MS-DOS is a U.S. registered trademark of Microsoft Corporation

**For more information, call your local HP sales office listed in your telephone directory or an HP regional office listed below for the location of your nearest sales office.**

**United States:**

800-452-4844

Hewlett-Packard Company  
4 Choke Cherry Road  
Rockville, MD 20850  
(301) 670-4300

Hewlett-Packard Company  
5201 Tollview Drive  
Rolling Meadows, IL 60008  
(708) 255-9800

Hewlett-Packard Company  
5651 W. Manchester  
Los Angeles, CA 90045  
(213) 337-8035

Hewlett-Packard Company  
2000 South Park Place  
Atlanta, GA 30339  
(404) 980-7351

**Canada:**

Hewlett-Packard Ltd.  
6877 Goreway Drive  
Mississauga, Ontario L4V 1M8  
(416) 678-9430

**Japan:**

Yokogawa-Hewlett-Packard Ltd.  
15-7, Nishi Shinjuku 4 Chome  
Shinjuku-ku  
Tokyo 160, Japan  
(03) 5371-1351

**Latin America:**

Hewlett-Packard  
Latin American Region Headquarters  
Monte Pelvoux No. 111  
Lomas de Chapultepec  
11000 Mexico, D.F.  
(525) 202-0155

**Australia/New Zealand:**

Hewlett-Packard Australia Ltd.  
31-41 Joseph Street  
Blackburn, Victoria 3130  
Australia (A.C.N. 004 394 763)  
(03) 895-2895

**Asia Pacific:**

Hewlett-Packard Asia Ltd.  
22/F Bond Centre  
West Tower  
89 Queensway  
Central, Hong Kong  
(852) 848 7777

**Europe/Africa/Middle East:**

Hewlett-Packard  
European Marketing Center  
P.O. Box 999  
1180 AZ Amstelveen  
The Netherlands  
(31) 20 547 9999

© Copyright 1991  
Hewlett-Packard Company  
Data subject to change  
Printed in U.S.A. 9/91  
5091-2348E