

VXLink Kit to Connect PC to C-size VXI HP E1483A

Technical Specifications

- External PC-based with WIN 3.1/WIN95 support
- High-performance PC-to-VXI interface
- Includes HP VIC, the VXI Installation Consultant
- Includes SICL and VISA I/O Libraries



Description

The HP E1483A VXLink provides a direct connection from your **PC to a VXI mainframe.** VXLink includes an ISA card that installs in your PC, a **C-size, 1-slot, message-based commander VXI module** that plugs into the VXI mainframe, and a 3-meter cable that connects the two. VXLink does not require a separate command module in the VXI mainframe; the VXLink VXI module goes into slot 0. System performance is greater than those VXI systems configured with a command module.

VXLink includes complete development software. The software includes EPConnect, SICL, VISA, I-SCPI drivers, and other software tools that dramatically reduce the time and effort required to develop and integrate your system. VXLink supports Interpreted SCPI (I-SCPI). (VXLink occupies 64 K of upper memory requiring 64 K of memory in either the D000 or E000 upper memory block.)

Refer to the HP Website directory of addresses (URLs) for instrument driver availability and downloading instructions.

Specifications

Interface Characteristics

Operating system: Win NT

Controller: PC-Based I/O library: SICL/VISA Backplane: ISA Max. I/O speed:

3.0 MB/s 16 bit:

32 bit: n/a

C/C++ Visual BASIC HP VEE Languages:

VXI Characteristics

VXI device type: Message-based Commander

Data transfer bus: n/a Size: С Slots: 1 P1/2 Connectors: **Shared memory:** n/a

TTL Trigger Bus (T) VXI busses:

C-size compatibility:

Module Current		
	I _{PM}	I _{DM}
+5 V:	2	0.45
+12 V:	0	0
−12 V:	0	0
+24 V:	0	0
−24 V:	0	0
−5.2 V:	0.1	0.03
−2 V:	0	0

Cooling/Slot

Watts/slot: 10.50 ΔP mm H_2O : 0.12 Air Flow liter/s: 0.80

Ordering Information

Description	Product No.
VXLink kit to connect PC to C-size VXI	HP E1483A
3 yr. retn. to HP to 1 yr. OnSite warr.	HP E1483A W01

Instrument Drivers

See the HP Website (http://www.hp.com/go/inst_drivers) for driver availability and downloading.

n/a

n/a

Yes

n/a

n/a

n/a

n/a

No


No

Command module firmware: **Command module** firmware rev: I-SCPI Win 3.1: I-SCPI Series 700: C-SCPI LynxOS: C-SCPI Series 700: **HP VEE Drivers:** VXI*plug&play* Win Framework:

VXI*plug&play* Win95/NT Framework:

VXI plug&play HP-UX

Framework: n/a



The VX Link Connection

Note: VX Link must use slot 0 in the VXI mainframe; limited to 1 UX Link per pc. VX Link is not compatible with the HP E1482B VXI bus extender.

Data Subject to Change Copyright © January 1997 Hewlett Packard Co.

HP Publication No.: 5965-5522E