



DC-BLOCK

DCZ(MIF)24(MIF)24 SERIES



Features

- Input 4 KHz to 65.0 GHz
- 2.40 mm Connectors
- Non-Resonant

Electrical Specifications - Specifications guaranteed from -55 to +100°C, measured in a 50-Ohm system

Parameter	FREQ. RANGE	Min	Typ	Max
Insertion Loss (dB)	4 KHz to 65.0 GHz		.7	
Rise Time (ps)			<5	
Group Delay (ps)			85	
DC Voltage (V)				16
RF Power (W)				1

Part Number Options

Please specify package style by adding to model number.	
Package Style(s)	Example
DCZM24F24 (Male 2.40/Female 2.40) DCZM24M24 (Male 2.40/Male 2.40) DCZF24F24 (Female 2.40/Female 2.40)	DCZM24F24

Marki Microwave reserves the right to make changes to the product(s) or information contained herein without notice. Marki Microwave makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Marki Microwave assume any liability whatsoever arising out of the use of or application of any product.




DC-BLOCK

Page 2


DCZ(MIF)24(MIF)24 SERIES

Input 4 KHz to 65.0 GHz


Typical Performance



DCZM24F24



DCZM24M24



DCZF24F24

DATA SHEET NOTES:

1. Specifications are subject to change without notice. Contact Marki Microwave for the most recent specifications and data sheets.

Marki Microwave reserves the right to make changes to the product(s) or information contained herein without notice. Marki Microwave makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does Marki Microwave assume any liability whatsoever arising out of the use or application of any product.

© Marki Microwave, Inc.



215 Vineyard Court, Morgan Hill, CA 95037 | Ph: 408.778.4200 | Fax 408.778.4300 | info@markimicrowave.com

www.markimicrowave.com