


MFBP-00006PSM

Passive GaAs MMIC 8.20-13.50 GHz Bandpass Filter

DEVICE OVERVIEW

General Description

The MFBP-00006PSM family of passive MMIC surface mount bandpass filters are an ideal solution for small form factor, high rejection filtering. Passive GaAs MMIC technology allows production of smaller filter constructions that replace larger form factor circuit board constructions. Tight fabrication tolerances allow for less unit-to-unit variation than traditional filter technologies. The MFBP-00006PSM is available as a 5x5mm plastic QFN. Low unit to unit variation allows for accurate simulations using the provided S2P file taken from measured production units.



[Download s-parameters here](#)

Features

- Excellent Return Loss
- High Stop Band Suppression
- Wide Stop Band with Fast Roll-Off

Applications

N/A

Functional Block Diagram



Part Ordering Options

Part Number	Description	Package	Packing Size	Green Status	Product Lifecycle	Export Classification
EVB-MFBP-00006P	Evaluation Board, Passive GaAs 8.20-13.50 GHz MMIC Bandpass Filter	-	-	RoHS REACH	Released	EAR99
MFBP-00006PSM	Passive GaAs MMIC 8.20-13.50 GHz Bandpass Filter	PSM	-	RoHS REACH	Released	EAR99

MFBP-00006PSM

Passive GaAs MMIC 8.20-13.50 GHz Bandpass Filter

Table Of Contents

■ Device Overview

- General Description
- Features
- Applications
- Functional Block Diagram

■ Port Configuration and Functions

- Port Diagram
- Port Functions

■ Specifications

- Absolute Maximum Ratings
- Package Information
- Electrical Specifications
- Typical Performance Plots

■ Mechanical Data


- Outline Drawing

■ Footprint Image


Port Configuration and Functions

Port Diagram

A top-down x-ray view of the MFBP-00006PSM package outline drawing is shown below. The MMIC bandpass filters are symmetrical allowing Pin 5 or Port 20 to be used as the input.



Port Functions

Port	Function	Description	Equivalent Circuit for Package
Pad	Ground	PSM package ground path is provided through the substrate and ground bond pads.	
Pin 20	Input/Output	Pin 20 is DC open to ground for the PSM package.	
Pin 5	Input/Output	Pin 5 is DC open to ground for the PSM package.	

Specifications

Absolute Maximum Ratings

The Absolute Maximum Ratings indicate limits beyond which damage may occur to the device. If these limits are exceeded, the device may be inoperable or have a reduced lifetime.

Parameter	Maximum Rating	Unit
Maximum Operating Temperature	100	°C
Maximum Storage Temperature	125	°C
Minimum Operating Temperature	-55	°C
Minimum Storage Temperature	-65	°C

Package Information

Parameter	Details	Rating
Dimensions	-	5x5 mm

MFBP-00006PSM

Passive GaAs MMIC 8.20-13.50 GHz Bandpass Filter

Electrical Specifications






The electrical specifications apply at TA=+25°C in a 50Ω system. Typical data shown is for the filter in a PSM package with a sine wave input applied to Pin 5. Min and Max limits are guaranteed at TA=+25°C.

Parameter	Test Conditions	Minimum Frequency (GHz)	Maximum Frequency (GHz)	Min	Typ	Max	Unit
1dBc Passband Low Frequency	-	-	-	-	8.2	-	GHz
1dBc Passband High Frequency	-	-	-	-	13.5	-	GHz
3dBc Passband Low Frequency	-	-	-	-	7.7	-	GHz
3dBc Passband High Frequency	-	-	-	-	14.05	-	GHz
Passband Return Loss	-	8.2	13.5	-	18	-	dB
Stopband Suppression	-	0	5.1	35	55	-	dB
Stopband Suppression	-	17.7	40	35	49	-	dB
Group Delay	-	-	-	-	250	-	ps
Impedance	-	-	-	-	50	-	Ω
Center Frequency, f_c	-	-	-	-	10.2	-	GHz
Insertion Loss @ F_c	-	10.2	10.2	-	1.83	-	dB

MFBP-00006PSM

Passive GaAs MMIC 8.20-13.50 GHz Bandpass Filter

Typical Performance Plots




MFBP-00006PSM

Passive GaAs MMIC 8.20-13.50 GHz Bandpass Filter

Mechanical Data

Outline Drawing





MFBP-00006PSM

Passive GaAs MMIC 8.20-13.50 GHz Bandpass Filter

Footprint Image

QFN 5mm Sample Drawing
X-Ray view



Material Rogers 4003 008" $\frac{1}{2}$ Oz Cu both sides.

MFBP-00006PSM

Passive GaAs MMIC 8.20-13.50 GHz Bandpass Filter






Evaluation Board - Performance Data

Parameter	Test Conditions	Frequency Range (GHz)	Min	Typ	Max	Unit
3dBc Passband Low Frequency	-	-	-	7.7	-	GHz
Group Delay	-	-	-	250	-	ps
1dBc Passband Low Frequency	-	-	-	8.2	-	GHz
Stopband Suppression	-	0 - 5.1	35	55	-	dB
Insertion Loss @ F_c	-	10.2 - 10.2	-	1.83	-	dB
1dBc Passband High Frequency	-	-	-	13.5	-	GHz
Stopband Suppression	-	17.7 - 40	35	49	-	dB
3dBc Passband High Frequency	-	-	-	14.05	-	GHz
Center Frequency, f_c	-	-	-	10.2	-	GHz
Impedance	-	-	-	50	-	Ω
Passband Return Loss	-	8.2 - 13.5	-	18	-	dB


MFBP-00006PSM

Passive GaAs MMIC 8.20-13.50 GHz Bandpass Filter

Evaluation Board - Typical Performance Plots



MFBP-00006PSM
Passive GaAs MMIC 8.20-13.50 GHz Bandpass
Filter



MFBP-00006PSM

Passive GaAs MMIC 8.20-13.50 GHz Bandpass Filter

DISCLAIMER

MARKI MICROWAVE, INC., ("MARKI") PROVIDES TECHNICAL SPECIFICATIONS AND DATA (INCLUDING DATASHEETS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, AND OTHER INFORMATION AND RESOURCES "AS IS" AND WITH ALL FAULTS. MARKI DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT.

These resources are intended for developers skilled in the art designing with Marki products. You are solely responsible for (1) selecting the appropriate products for your application, (2) designing, validating, and testing your application, and (3) ensuring your application meets applicable standards and other requirements. Marki makes no guarantee regarding the suitability of its products for any particular purpose, nor does Marki assume any liability whatsoever arising out of your use or application of any Marki product.

Marki grants you permission to use these resources only for development of an application that uses Marki products. Other reproduction or use of these resources is strictly prohibited. No license is granted to any other Marki intellectual property or to any third-party intellectual property. Marki reserves the right to make changes to the product(s) or information contained herein without notice.

MARKI MICROWAVE and T3 MIXER are trademarks or registered trademarks of Marki Microwave, Inc. All other trademarks used are the property of their respective owners.

© 2023, Marki Microwave, Inc