


MFBP-00150PSM

Passive GaAs MMIC 2.8 - 4.6 GHz Bandpass Filter

DEVICE OVERVIEW

General Description

The MFBP-00150PSM passive MMIC surface mount bandpass filter is an ideal solution for small form factor, high rejection filtering. The MFBP-00150PSM features a 2.8-4.6GHz 1dBc passband and 1.9dB center frequency insertion loss. Passive GaAs MMIC technology allows production of smaller filter constructions that replace larger form factor circuit board constructions. Tight fabrication tolerances allow for less unit-to-unit variation than traditional filter technologies. The MFBP-00150PSM is available as a 5 mm plastic QFN. Low unit to unit variation allows for accurate simulations using the provided S2P file taken from measured production units.



[Download s-parameters here](#)

Features

- 25 dB Return Loss
- 1.9 dB Insertion Loss @ Fc
- High Stop Band Suppression
- Wide Stop Band with Fast Roll-Off

Applications

N/A

Functional Block Diagram



Part Ordering Options

Part Number	Description	Package	Green Status	Product Lifecycle	Export Classification
MFBP-00150PSM	Passive GaAs MMIC 2.8 - 4.6 GHz Bandpass Filter	PSM	RoHS REACH	Released	EAR99
EVB-MFBP-00150P	Evaluation Board, Passive GaAs 2.8 - 4.6 GHz MMIC Bandpass Filter	EVB	RoHS REACH	Released	EAR99

Table Of Contents


■ Device Overview General Description Features Applications Functional Block Diagram	■ Specifications Absolute Maximum Ratings Package Information Electrical Specifications Typical Performance Plot
■ Port Configuration and Functions Port Diagram Port Functions	■ Mechanical Data Outline Drawing
■ Revision History	■ Footprint Image
	■ Evaluation Board Evaluation Board Outline Drawing

Revision History


Revision Code	Revision Date	Comment
-	2025-10-06	Initial Release

Port Configuration and Functions

Port Diagram



Port Functions

Port	Function	Description	DC Equivalent Circuit
Ground Paddle	Ground	PSM package ground path is provided through the ground paddle and should be connected to RF ground.	
Pin 20	Input/Output	Pin 20 is DC open to ground for the PSM package.	
Pin 5	Input/Output	Pin 5 is DC open to ground for the PSM package.	

Specifications

Absolute Maximum Ratings

The Absolute Maximum Ratings indicate limits beyond which damage may occur to the device. If these limits are exceeded, the device may be inoperable or have a reduced lifetime.

Parameter	Maximum Rating	Unit
Maximum Operating Temperature	100	°C
Maximum Storage Temperature	125	°C
Minimum Operating Temperature	-55	°C
Minimum Storage Temperature	-65	°C

Package Information





Parameter	Details	Rating
ESD	250 to < 500 Volts	HBM Class 1A
Dimensions	-	5 x 5 mm
Moisture Sensitivity Level	-	MSL 1

Electrical Specifications

The electrical specifications apply at TA=+25°C in a 50Ω system. Typical data shown is for the filter in a PSM package with a sine wave input applied to Pin 5. Min and Max limits are guaranteed at TA=+25°C.

Parameter	Test Conditions	Minimum Frequency (GHz)	Maximum Frequency (GHz)	Min	Typ	Max	Unit
1 dBc Passband	Configuration A, Temp = 25°C	2.81	4.62	-	-	-	GHz
3 dBc Passband	Configuration A, Temp = 25°C	2.57	4.88	-	-	-	GHz
30 dBc Rejection Point	Configuration A, Temp = 25°C	2.3	5.32	-	-	-	GHz
Center Freq	Configuration A, Temp = 25°C	-	-	-	3.60	-	GHz
Insertion Loss @ fc	Configuration A, Temp = 25°C	-	-	-	1.9	-	dB
Passband Return Loss	Configuration A, Temp = 25°C	-	-	-	25	-	dB
Group Delay	Configuration A, Temp = 25°C	-	-	-	504	-	ps
Impedance	Configuration A, Temp = 25°C	-	-	-	50	-	Ω

Typical Performance Plot




All measurements are de-embedded from the fixture with Automatic Fixture Removal (AFR).

Mechanical Data

Outline Drawing

Download : [Outline 2D Drawing](#)





MFBP-00150PSM

Passive GaAs MMIC 2.8 - 4.6 GHz Bandpass Filter

Footprint Image


Download : [Footprint Drawing](#)

QFN 5mm Sample Drawing
X-Ray view



Material Rogers 4003 008" $\frac{1}{2}$ Oz Cu both sides.

Evaluation Board - Outline Drawing



DISCLAIMER

MARKI MICROWAVE, INC., ("MARKI") PROVIDES TECHNICAL SPECIFICATIONS AND DATA (INCLUDING DATASHEETS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, AND OTHER INFORMATION AND RESOURCES "AS IS" AND WITH ALL FAULTS. MARKI DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT.

These resources are intended for developers skilled in the art designing with Marki products. You are solely responsible for (1) selecting the appropriate products for your application, (2) designing, validating, and testing your application, and (3) ensuring your application meets applicable standards and other requirements. Marki makes no guarantee regarding the suitability of its products for any particular purpose, nor does Marki assume any liability whatsoever arising out of your use or application of any Marki product.

Marki grants you permission to use these resources only for development of an application that uses Marki products. Other reproduction or use of these resources is strictly prohibited. No license is granted to any other Marki intellectual property or to any third-party intellectual property. Marki reserves the right to make changes to the product(s) or information contained herein without notice.

MARKI MICROWAVE and T3 MIXER are trademarks or registered trademarks of Marki Microwave, Inc. All other trademarks used are the property of their respective owners.

© 2025, Marki Microwave, Inc