

MFLP-00045GSM2

Passive Glass 4.9 GHz Surface Mount Lowpass Filter

DEVICE OVERVIEW

General Description

The MFLP-00045GSM2 surface-mount lowpass filter is an ideal solution for extremely small form factor, high rejection filtering. The MFLP-00045GSM2 features a 4.9 GHz 3 dBc cutoff and 25 dB passband return loss. Its advanced glass substrate technology allows production of smaller filter constructions that replace larger form factor circuit board constructions. Tight fabrication ensures tighter unit-to-unit consistency than legacy filter technologies, supporting accurate simulation with the provided S2P data. The MFLP-00045GSM2 is offered in a 4.27 × 4.00 mm package.



[Download s-parameters here](#)


Features

- Low Passband Insertion Loss with Fast Roll-off
- 25 dB Return Loss
- High Stop Band Suppression

Applications

N/A

Functional Block Diagram



Part Ordering Options

Part Number	Description	Package	Green Status	Product Lifecycle	Export Classification
MFLP-00045GSM2	Passive Glass 4.9 GHz Surface Mount Lowpass Filter	GSM2	RoHS	Released	EAR99
EVB-MFLP-00045G	EVB-MFLP-00045G	GSM		Released	-

MFLP-00045GSM2

Passive Glass 4.9 GHz Surface Mount Lowpass Filter

Table Of Contents

■ Device Overview	■ Specifications
General Description	Absolute Maximum Ratings
Features	Package Information
Applications	Electrical Specifications
Functional Block Diagram	Typical Performance Plot
	Performance Over Temperature
■ Port Configuration and Functions	■ Mechanical Data
Port Functions	Outline Drawing
■ Revision History	■ Footprint Image
	■ Evaluation Board
	Evaluation Board Outline Drawing

Revision History



Revision Code	Revision Date	Comment
-	2025-12-10	Initial Release

MFLP-00045GSM2

Passive Glass 4.9 GHz Surface Mount Lowpass Filter

Port Configuration and Functions

Port Functions

Port	Function	Description	DC Equivalent Circuit
Pin 1	RF Input	Pin 1 is DC Open to GND and DC Short to Pin 2	
Pin 2	RF Output	Pin 2 is DC Open to GND and DC Short to Pin 1	

MFLP-00045GSM2

Passive Glass 4.9 GHz Surface Mount Lowpass Filter

Specifications

Absolute Maximum Ratings

Parameter	Maximum Rating	Unit
DC Current	2	A
Maximum Operating Temperature	100	°C
Maximum Storage Temperature	125	°C
Minimum Operating Temperature	-55	°C
Minimum Storage Temperature	-65	°C
RF Power Handling	4	W

Package Information

Parameter	Details	Rating
ESD	250 to < 500 Volts	HBM Class 1A
Dimensions	-	4.25 x 4.00 mm
Moisture Sensitivity Level	-	MSL 1

MFLP-00045GSM2

Passive Glass 4.9 GHz Surface Mount Lowpass Filter





Electrical Specifications

Parameter	Test Conditions	Minimum Frequency (GHz)	Maximum Frequency (GHz)	Min	Typ	Max	Unit
1 dBc Passband	Configuration A, Temp = 25°C	-	4.39	-	-	-	GHz
3 dBc Passband	Configuration A, Temp = 25°C	-	4.92	-	-	-	GHz
30 dBc Rejection Point	Configuration A, Temp = 25°C	-	5.45	-	-	-	GHz
Center Freq	Configuration A, Temp = 25°C	-	-	-	2.19	-	GHz
Passband Return Loss	Configuration A, Temp = 25°C	-	-	-	25	-	dB
Group Delay	Configuration A, Temp = 25°C	-	-	-	153	-	ps

MFLP-00045GSM2

Passive Glass 4.9 GHz Surface Mount Lowpass Filter

Typical Performance Plot



Performance Over Temperature




MFLP-00045GSM2

Passive Glass 4.9 GHz Surface Mount Lowpass Filter

Mechanical Data

Outline Drawing

Download : [Outline 2D Drawing](#)




MFLP-00045GSM2

Passive Glass 4.9 GHz Surface Mount Lowpass Filter

Footprint Image


Download : [Footprint Drawing](#)



MFLP-00045GSM2

Passive Glass 4.9 GHz Surface Mount Lowpass Filter

Evaluation Board - Outline Drawing



DISCLAIMER

MARKI MICROWAVE, LLC., ("MARKI") PROVIDES TECHNICAL SPECIFICATIONS AND DATA (INCLUDING DATASHEETS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, AND OTHER INFORMATION AND RESOURCES "AS IS" AND WITH ALL FAULTS. MARKI DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT.

These resources are intended for developers skilled in the art designing with Marki products. You are solely responsible for (1) selecting the appropriate products for your application, (2) designing, validating, and testing your application, and (3) ensuring your application meets applicable standards and other requirements. Marki makes no guarantee regarding the suitability of its products for any particular purpose, nor does Marki assume any liability whatsoever arising out of your use or application of any Marki product.

Marki grants you permission to use these resources only for development of an application that uses Marki products. Other reproduction or use of these resources is strictly prohibited. No license is granted to any other Marki intellectual property or to any third-party intellectual property. Marki reserves the right to make changes to the product(s) or information contained herein without notice.

MARKI MICROWAVE and T3 MIXER are trademarks or registered trademarks of Marki Microwave, LLC. All other trademarks used are the property of their respective owners.

© 2025, Marki Microwave, LLC