

PD4-0140


Ultra-Wideband 4-Way Wilkinson Power Divider

DEVICE OVERVIEW

General Description

4-Way Wilkinson power dividers can be used for both in-phase power splitting and power combining applications. These power dividers are realized as a cascade of two 1:2 Wilkinson power dividers integrated into a single package. 4-Way Wilkinson power dividers feature the lowest insertion loss (ideally 4 dB 4-way splitting loss), excellent amplitude and phase balance, and high isolation across the entire operating band.

[Download s-parameters here](#)




Features

- 1 to 40 GHz In-phase Power Splitting
- Outstanding Output to Output Isolation
- Outstanding Phase and Amplitude Balance

Applications

N/A

Functional Block Diagram



Part Ordering Options

Part Number	Description	Package	Packing Size	Green Status	Product Lifecycle	Export Classification
PD4-0140	Ultra-Wideband 4-Way Wilkinson Power Divider	-	-	RoHS	Released	EAR99

Table Of Contents

■ Device Overview

- General Description
- Features
- Applications
- Functional Block Diagram

■ Port Configuration and Functions

- Port Functions

■ Revision History

■ Specifications

- Absolute Maximum Ratings
- Package Information
- Electrical Specifications
- Typical Performance Plots

■ Mechanical Data

- Outline Drawing

Revision History

Revision Code	Revision Date	Comment
-	2018-11-27	Datasheet Initial Release

Port Configuration and Functions

Port Functions

Port	Function	Description	Equivalent Circuit for Package
In	Divider Common Input	Wilkinson Divider Common Input.	-
Out 1	Divider Output 1	RF divided output 1 of the Wilkinson divider.	-
Out 2	Divider Output 2	RF divided output 2 of the Wilkinson divider.	-
Out 3	Divider Output 3	RF divided output 3 of the Wilkinson divider.	-
Out 4	Divider Output 4	RF divided output 4 of the Wilkinson divider.	-

Specifications

Absolute Maximum Ratings

Parameter	Maximum Rating	Unit
RF Power Handling as a Power Combiner	1	W
RF Power Handling as a Power Divider	10	W

Package Information

Parameter	Details	Rating
Weight	-	220g
Dimensions	-	120.4 × 67.3 mm

Electrical Specifications

Specifications guaranteed from -55 to +100°C, measured in a 50Ω system.



Parameter	Test Conditions	Minimum Frequency (GHz)	Maximum Frequency (GHz)	Min	Typ	Max	Unit
Phase Balance	-	1	40	-	4	15	°
Insertion Loss ¹	-	1	40	-	2.5	-	dB
VSWR	-	1	40	-	1.55	-	-
Isolation	-	1	1.6	10	-	-	dB
Isolation	-	1.6	36	15	20	-	dB
Isolation	-	36	40	10	-	-	dB
Weight	-	-	-	-	220	-	g
Amplitude Balance	-	1	40	-	0.4	1.2	dB
Nominal Phase Balance	-	1	40	-	0	-	°
Nominal Power Splitting (dB)	-	1	40	-	6	-	dB

^[1] Excess Insertion Loss = (Input Port to Common Port Insertion Loss) - 6dB

PD4-0140

Ultra-Wideband 4-Way Wilkinson Power Divider

Typical Performance Plots




PD4-0140

Ultra-Wideband 4-Way Wilkinson Power Divider

Mechanical Data

Outline Drawing



DISCLAIMER

MARKI MICROWAVE, INC., ("MARKI") PROVIDES TECHNICAL SPECIFICATIONS AND DATA (INCLUDING DATASHEETS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, AND OTHER INFORMATION AND RESOURCES "AS IS" AND WITH ALL FAULTS. MARKI DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT.

These resources are intended for developers skilled in the art designing with Marki products. You are solely responsible for (1) selecting the appropriate products for your application, (2) designing, validating, and testing your application, and (3) ensuring your application meets applicable standards and other requirements. Marki makes no guarantee regarding the suitability of its products for any particular purpose, nor does Marki assume any liability whatsoever arising out of your use or application of any Marki product.

Marki grants you permission to use these resources only for development of an application that uses Marki products. Other reproduction or use of these resources is strictly prohibited. No license is granted to any other Marki intellectual property or to any third-party intellectual property. Marki reserves the right to make changes to the product(s) or information contained herein without notice.

MARKI MICROWAVE and T3 MIXER are trademarks or registered trademarks of Marki Microwave, Inc. All other trademarks used are the property of their respective owners.

© 2018, Marki Microwave, Inc