



PRODUCT SPECIFICATION

PS-ES0189 REV -

MODEL NO.ES0189 SPDT SWITCH

PARAMETER	VALUE	UNITS
1.0 High Power Input Specifications		-
1.1 Frequency Range	2.4-2.5	GHz
1.2 Power, Peak (nominal)	10	Watts
1.3 Power, Average (nominal)	10	Watts
1.4 Duty (Maximum)	CW	%
1.5 RF Pulse Width (Maximum)	CW	us
1.6 Load VSWR (Maximum)	2.5:1	-

2.0 Microwave Switch Specifications		-
2.1 Frequency Range	2.4	GHz
2.2 Isolation (Minimum)	55	dB
2.3 Insertion Loss (Maximum)	0.6	dB
2.4 VSWR (Input)	1.5:1	-
2.5 RF Switching Speed (Maximum)	0.5	us
2.6 Control Switching Freq. (Maximum)	100KHz	KHz

3.0 General Specifications

3.1 Connectors		-
3.1.1 RF	SMA	
3.1.2 Control/Bias	SMA/PINS	
3.2 Logic,	TTL	
3.2.2 State Table		

<u>TTL CNTL</u>	<u>RF Path</u>
" 0 "	J1 to J2
" 1 "	J1 to J3

3.3 DC Power Requirements

3.3.1 Positive Supply	+5+/-5%	Vdc
3.3.2 Positive Supply Current (Max)	300	mA
3.3.3 Negative Supply Voltage	-28v +/-5%	Vdc
3.3.4 Negative Supply Current (max)	100	mA

3.4 Environmental

3.4.1 Temperature		
3.4.1.1 Operating	-40 to +85	Degrees C
3.4.1.2 Storage	-55 to +125	Degrees C
3.4.2 Cooling: Conduction cooling through surface of switch body		

3.5 Dimensions Refer to ES0189 outline drawing

=====

ENG:_____	MFG ENG:_____	TEST ENG:_____	QC:_____
DATE:_____	DATE :_____	DATE :_____	DATE:_____

=====