




VigraVision STD

Technical Specifications



VigraVision® STD products are versatile frame grabbers with the added power of on-board graphics capabilities and support of live video in a graphics window. The flexible image acquisition and analog camera interface, as well as the video outputs with graphic overlay capabilities are included. VigraVision STD is available in both PMC and PCI form factors.



VigraVision STD Technical Specifications

Form Factor			
PMC	32-bit/33 MHz		
PCI	32-bit/64 MHz		
Graphics Processor	S3 Savage 4		
Memory	16 MB SDRAM		
1/0	Input	Output	
S-Video	•	•	
RS170-A	•	•	
NTSC	•	•	
PAL	•	•	
RGB		•	
TV-Out (S-Video and RS170-A)		•	
Display			
# Simultaneous Displays	1		
Max Resolution Rates	1600 x 1200		
Refresh Rates	Up to 85 Hz		
Operating System Software			
Windows 95	•		
Windows 98	•		
Windows 2000	•		
Windows NT	•		
Solaris	•		
VxWorks	•		
Linux (PCI only)	•		
Vigra Software Tools			
VigraVision Toolbox	•		
VigraX	•		
Environmental			
Operating Temp	0 to 50 C		
Storage Temp	-20 to 85 C		
Humidity	0 to 90% (non-conde	0 to 90% (non-condensing)	
Max Power Consumption	12 W		
MTBF	40,000 hours (calcula	40,000 hours (calculated)	

Ordering Information

DoD/OFOISR Cleared #06-S-1678

For additional information, visit our website at www.L-3Com.com/apd, keyword search "Vigra". Or contact us via email at apd-info@L-3Com.com, via phone at 800.621.8474 or 858.552.9500.

Note: Information contained herein is subject to change without notice. Contact L-3 Communications Advanced Products & Design for the latest technical specifications. All trademarks and/or registered trademarks are the property of their respective companies. Military photos courtesy of Department of Defense.

MKTG VVSTD022306

L-3 Communications Advanced Products & Design 3033 Science Park Road San Diego, CA 92121

Tel: 800.621.8474 858.552.9500 Fax: 858.535.3609 apd-info@L-3Com.com www.L-3Com.com/apd

