

ADVANCE INFORMATION

September 2003

LM96010

Hardware Monitor with Dual Thermal Diodes and SensorPath™ Bus

General Description

The LM96010 is part of a hardware monitor system, comprised of two parts the Super I/O (Master) and LM96010 (slave). The LM96010 will be controlled by the Master and report to the master temperature, and voltage measurements using the SensorPath $^{\rm TM}$ single-wire bus. The LM96010 measures the temperature of its own die as well as two external devices such as a processor thermal diode or a diode connected transistor. The LM96010 can resolve temperatures up to 140 °C and down to -55 °C. Using $\Sigma\Delta$ ADC it measures Vccp, +2.5V, +3.3V, +5V and +12V analog input voltages with internal scaling resistors.

Features

- SensorPath Interface
 - 2 hardware programmable addresses
- Voltage Monitoring
 - 9-bit ΣΔ ADC
 - Internal scaling resistors for all inputs
 - Monitors Vccp, +2.5 V, +3.3 V, +5 V and +12 V
- Temperature Sensing

- 2 remote diode temperature sensor zones
- Internal local temperature zone
- 0.5 °C resolution
- Measures temperatures up to 140 °C
- 14-lead TSSOP package

Key Specifications

■ Voltage Measurement Accuracy
 ±2 % (max)
 Temperature Sensor Accuracy
 ±3 °C (max)

■ Temperature Range:

─ LM96010 junction
 ─ Remote Temp Accuracy
 0 °C to +85 °C
 +25 °C to +100 °C

■ Power Supply Voltage +3.0 V to +3.6 V


■ Average Power Supply Current 0.5 mA (typ)

■ Round-robin Conversion of All Channels 182 ms

Applications


 Microprocessor based equipment (Motherboards, Video Cards, Base-stations, Routers, ATMs, Point of Sale, ...)

Typical Application



SensorPath™ is a trademark of National Semiconductor Corporation

Block Diagram



LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT AND GENERAL COUNSEL OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

- Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
- A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

BANNED SUBSTANCE COMPLIANCE

National Semiconductor certifies that the products and packing materials meet the provisions of the Customer Products Stewardship Specification (CSP-9-111C2) and the Banned Substances and Materials of Interest Specification (CSP-9-111S2) and contain no "Banned Substances" as defined in CSP-9-111S2.



National Semiconductor Americas Customer Support Center

Email: new.feedback@nsc.com Tel: 1-800-272-9959

www.national.com

National Semiconductor Europe Customer Support Center Fax: +49 (0) 180-530 85 86

Email: europe.support@nsc.com
Deutsch Tel: +49 (0) 69 9508 6208
English Tel: +44 (0) 870 24 0 2171
Français Tel: +33 (0) 1 41 91 8790

National Semiconductor Asia Pacific Customer Support Center Email: ap.support@nsc.com National Semiconductor Japan Customer Support Center Fax: 81-3-5639-7507 Email: jpn.feedback@nsc.com Tel: 81-3-5639-7560