

TopMap TMS-600/650



WHITE LIGHT INTERFEROMETER TMS-SERIES

- TopCam
TMS-300/320
- TopMap
TMS-500
- TopMap
TMS-600/650

LARGE AREA FLATNESS AND TOPOGRAPHY MEASUREMENT WITH NANOMETER RESOLUTION

Polytec offers with his high precision white light interferometer of the TMS-600/650 series a measurement systems for topography and flatness measurements with high z-dynamic and a vertical resolution of a few nanometer.

High-precision and fast

The TopMap TMS-600/650 white light interferometer is the perfect measurement system if there is a need for measurements of high precision technical surfaces. 455.000 points at once provides measurement times for areas up to 30 x 40 mm of a few seconds.

In consequence of the high z dynamic of 50 mm it is even possible to measure not flat surfaces. The required measurement time depends on the scanning way in z direction.

Caused by a technique which is called "Overlay" it is possible to measure even surfaces with high contrasts.

The telecentric lenses afford a measurement on steep edges and drilling holes.

TMS Software

The TMS Software includes all necessary handling and analysis function needs for a automatically operation.

2D and 3D mapping is also possible like the ability to add profile cuts and different filter algorithms.

Features

- High precision with z-resolution up to 1 nm
- High z-dynamic of 50 mm
- Flexible by Overlay technique
- Fast by field of views of 30 mm x 40 mm
- Contact less by optical interferometric set-up
- Measurements in drilling holes by telecentric lenses

Specifications

TopMap TMS-600/650 Hardware	
Interferometer type	Michelson (telecentric)
Field of views	7 x 10 mm ² , 15 x 20 mm ² , 30 x 40 mm ² (10 x 13 mm ² , 20 x 27 mm ² , 29 x 38 mm ²)*
Z-dynamic	50 mm
Z-resolution (TopMap TMS-600)	10 nm
Z-resolution (TopMap TMS-650)	1 nm
Lateral resolution	12 µm – 53 µm (9 µm – 29 µm)*
Camera-resolution	780 (H) x 582 (V) Pixel
High resolution camera**	1300 (H) x 1030 (V) Pixel
Dimensions	66 x 53 x 20 cm ³
Power	100 – 240 V
Weight	ca. 45 kg

* with high resolution camera, ** with high z-accuracy

TMS Software
Functional operator interface through PC control
Live video for placement and adjustment of the measurement sample
Versatile filter and interpolation algorithms
Easy interfacing via COM/ActiveX or LabView/DriverÜ

Polytec TMS white light interferometer overview							
	PC incl. software	z-dynamic 500 µm	z-dynamic 50 mm	high z- resolution	phase shift	high resolution camera	basic engine
TMS-300	•	•		•			◦
TMS-320	•		•	◦			◦
TMS-500	•		•			◦	◦
TMS-600	•		•	•		◦	•
TMS-650	•		•	•	•	◦	•

• standard ◦ optional available

Polytec GmbH

Polytec-Platz 1-7
76337 Waldbronn

Germany

Tel. + 49 (0) 7243 604-0
Fax + 49 (0) 7243 69944
info@polytec.de

Polytec-PI, S.A.

32 rue Délizy
93694 Pantin

France

Tel. + 33 (0) 1 48 10 39 34
Fax + 33 (0) 1 48 10 09 66
info@polytec-pi.fr

Lambda

Photometrics Ltd.

Lambda House, Batford Mill
Harpden, Herts AL5 5BZ

Great Britain

Tel. + 44 (0) 1582 764334
Fax + 44 (0) 1582 712084
info@lambdaphoto.co.uk

Polytec KK

Hakusan High Tech Park
1-18-2 Hakusan, Midori-ku
Yokohama-shi, 226-0006
Kanagawa-ken

Japan

Tel. +81 (45) 938-4960
Fax +81 (45) 938-4961
info@polytec.co.jp

Polytec, Inc.

North American Headquarters
1342 Bell Avenue, Suite 3-A
Tustin, CA 92780

USA

Tel. +1 714 850 1835
Fax +1 714 850 1831
info@polytec.com

Polytec, Inc.

East Coast Office
16 Albert Street
Auburn, MA 01501

USA

Tel. +1 508 832 0501
Fax +1 508 832 4667