



## High sensitive photodiodes

### General Description

The epc200 is a high-sensitive, high-speed, low-cost photo diode for light-barriers, light-curtains, and similar applications. These photo diodes are designed to be used in a reverse-bias mode, whereas the reverse bias voltage can be between 1.5 and 20 Volts. This device allows the design of short to long range light barriers from a few millimeters up to tens of meters.

The diodes feature a very high quantum efficiency of 90% in the near IR range, a reverse breakdown voltage of up to 30 Volts and a response time down to less than 100ns.

The advanced Chips Scale Package (CSP) makes this device ideal for miniaturized systems where a minimal space requirement is key.

### Features

- Low dark current
- High sensitivity
- High dynamic range
- CSP package with very small footprint
- Customer specific wavelength filter on request
- Fully standard SMD assembly process compatible

### Applications

- Light barriers and light curtains
- Light barriers ranging from millimeters to tens of meters
- Light curtains
- Smoke detectors
- Liquid detectors
- Heart beat monitors
- Oximeters
- Position detection (rotary, linear, angle, etc.)
- IR remote control of Hi-Fi, TV sets and other equipment

### Product image




Figure 1: epc200 photo diodes

Absolute Maximum Ratings (Notes 1, 2)		Recommended Operating Conditions			
Reverse Voltage $V_R$	30.0 V	Reverse Voltage ( $V_R$ )	Min. 1.5	Max. 20.0	Units V
Storage Temperature Range ( $T_s$ )	-40°C to +85°C	Operating Temperature ( $T_A$ )	-40	+85	°C
Lead Temperature solder, 4 sec. ( $T_L$ )	+260°C	Relative Humidity (non-condensing)	+5	+95	%
Expected Lifetime (MTBF)	500 * 10 <sup>6</sup> h @ 25°C (<2 FIT)				

**Note 1:** Absolute Maximum Ratings indicate limits beyond which damage to the device may occur. Recommended operating conditions indicate conditions for which the device is intended to be functional, but do not guarantee specific performance limits. For guaranteed specifications and test conditions, see Electrical Characteristics.


**Note 2:** This device is a highly sensitive CMOS photodiodes with an ESD rating of JEDEC HBM class 2 (2kV to <4kV). Handling and assembly of this device should only be done at ESD protected workstations.

## General Characteristics

Unless otherwise stated, measuring parameters are  $V_R = 5.0$  V,  $-40^\circ\text{C} < T_A < +85^\circ\text{C}$ ,  $R_L = 50 \Omega$

Symbol	Parameter	Conditions/Comments	Values			Units
			Min.	Typ.	Max.	
$\lambda_{S \text{ max.}}$	Wavelength	max. Sensitivity		850		nm
$\lambda$	Wavelength Range	$S = 20\%$ of $S_{\text{max}}$	450		1050	nm
$S_A$	Spectral Sensitivity	$\lambda = 850\text{nm}$ , $V_R = 5\text{V}$ , $I_e = 1 \text{ mW/cm}^2$ $\lambda = 950\text{nm}$ , $V_R = 5\text{V}$ , $I_e = 1 \text{ mW/cm}^2$		0.61 0.43		A/W A/W
$\eta$	Quantum Efficiency	$\lambda = 850\text{nm}$ , $V_R = 5\text{V}$ , $I_e = 1 \text{ mW/cm}^2$ $\lambda = 950\text{nm}$ , $V_R = 5\text{V}$ , $I_e = 1 \text{ mW/cm}^2$		90 62		%
$\phi$	Half angle			$\pm 60$		°
$V_O$	Open Circuit Voltage	$I_e = 0.5 \text{ mW/cm}^2$		250		mV
$TC_V$	Temperature Coefficient of $I_{SC}$			0.25		%/K
$TC_O$	Temperature Coefficient of $V_O$			-3.0		mV/K
$I_P$	Photo Current	$V_R = 5\text{V}$ , $I_e = 1 \text{ mW/cm}^2$ , $\lambda = 850 \text{ nm}$ $V_R = 5\text{V}$ , $I_e = 1 \text{ mW/cm}^2$ , $\lambda = 950 \text{ nm}$		18.7 13.2		$\mu\text{A}$
$I_R$	Dark Current	$V_R = 5 \text{ V}$ , $T_A = 20^\circ\text{C}$ $V_R = 20 \text{ V}$ , $T_A = 20^\circ\text{C}$ Selected types with reduced dark current on request		2 5	20	nA
$I_{SC}$	Short-circuit Current	$I_e = 1 \text{ mW/cm}^2$ , $\lambda = 850 \text{ nm}$		20		$\mu\text{A}$
$t_r$	Rise/Fall Time	$V_R = +1.5 \text{ V}$ $V_R = +5.0 \text{ V}$ $V_R = +10.0 \text{ V}$	photo current measured at $R_L = 50 \Omega$ , $\lambda = 850 \text{ nm}$ , $I_P = 200 \mu\text{A}$			ns
$C_O$	Capacitance	$V_R = +5\text{V}$ , $f = 100\text{kHz}$ , $E = 0$		22		pF
NEP	Noise Equivalent Power	$V_R = 5 \text{ V}$			$1.2 \times 10^{-14}$	W/ $\sqrt{\text{Hz}}$

## Connection Diagram




Pin	Assignment
1	Cathode
2	Cathode
3	Cathode
4	Cathode
5	Anode


Figure 2: Chip connections

## Other Parameters


(typical values,  $T_{amb} = 25^{\circ}\text{C}$ ,  $V_{DD} = 5.0\text{V}$ ,  $I_{PD}=0\text{mA}$ )




Relative sensitivity vs. illumination angle



Relative spectral sensitivity (no daylight filter)



Photocurrent  $I_P = f(I_e)$ ,  $V_R = 5\text{V}$ ,  $\lambda = 850\text{nm}$



Rise / fall time versus reverse bias voltage



## Packaging Information

(all measures in mm)

### CSP5 Tape




Figure 6: Carrier tape dimensions & chip orientation

### Tape & Reel Information

The devices are mounted on embossed tape for automatic placement systems. The tape is wound on 330 mm (13 inch) reels and individually packaged for shipment. General tape-and-reel specification data are available in a separate data sheet and indicate the tape sizes for various package types. Further tape-and-reel specifications can be found in the Electronic Industries Association (EIA) standard 481-1, 481-2, 481-3.

epc does not guarantee non-empty cavities. Thus, pick-and-place machines should check the presence of a chip during picking.

It is highly recommended to use underfill after assembly of the chips to the PCB.

## Ordering Information

Part Name	Part Number	Package	RoHS compliance	Packaging Method
epc200-CSP5	P100 179	CSP5	Yes	Reel
epc200 Chip Carrier	P100 205	PCB	Yes	Tray Tape on request




Figure 7: epc200 photo diodes on chip carrier

## IMPORTANT NOTICE

ESPROS Photonics AG and its subsidiaries (epc) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to epc's terms and conditions of sale supplied at the time of order acknowledgment.

epc warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with epc's standard warranty. Testing and other quality control techniques are used to the extent epc deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

epc assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using epc components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

epc does not warrant or represent that any license, either express or implied, is granted under any epc patent right, copyright, mask work right, or other epc intellectual property right relating to any combination, machine, or process in which epc products or services are used. Information published by epc regarding third-party products or services does not constitute a license from epc to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from epc under the patents or other intellectual property of epc.

Resale of epc products or services with statements different from or beyond the parameters stated by epc for that product or service voids all express and any implied warranties for the associated epc product or service. epc is not responsible or liable for any such statements.

epc products are not authorized for use in safety-critical applications (such as life support) where a failure of the epc product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of epc products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by epc. Further, Buyers must fully indemnify epc and its representatives against any damages arising out of the use of epc products in such safety-critical applications.

epc products are neither designed nor intended for use in military/aerospace applications or environments unless the epc products are specifically designated by epc as military-grade or "enhanced plastic." Only products designated by epc as military-grade meet military specifications. Buyers acknowledge and agree that any such use of epc products which epc has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

epc products are neither designed nor intended for use in automotive applications or environments unless the specific epc products are designated by epc as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, epc will not be responsible for any failure to meet such requirements.