

XS40 LIGHT

XS Series with Internal Driver




ELECTRICAL:

Input Voltage: 12 to 26.4VDC
 Input Current: 260mA typical (1.2A max for burst) @24VDC
 460mA typical (2.5A max for burst) @12VDC
Note: Power supply must be capable of 1.2A per light for burst feature to work correctly with supplied cable.

Strobe Input Impedance: 10KΩ – PNP typical, 9.1KΩ – NPN typical
 Strobe Timing: <5 microseconds from strobe to LED on
 0-10V Input Impedance: 15KΩ typical
 0-10V Input Control: 0V = 100%, 10V = 0% LED current. (Can be left disconnected for 100% LED current)
 Variable Intensity: Adjustable via trim potentiometer from 0% (CCW) to 100% (CW).
 Over-temperature LED: 70 ± 5°C strobe disable / "Error" LED on; 5°C hyst. for strobe enable / "Error" LED off

Wiring:

Pin #	Wire Color	Function
1	Brown	+12 to +26.4VDC
2	White	NPN STROBE INPUT: GND for "ON", Open or >Vin-1V for "OFF"
3	Blue	0VDC (DC GND)
4	Black	PNP STROBE INPUT: < 1 VDC for "OFF", >3 ≤30 VDC for "ON"
5	Grey	0-10VDC analog intensity control – 0V = 100%, 10V = 0%



ENVIRONMENTAL:

Operating Temperature: 0 to 40°C
 Relative Humidity: 5 to 85% non-condensing

MECHANICAL:

Lighted Area: 40mm
 Connector: M12 - 5 pin
 Weight: 3.88 oz (110g)

ILLUMINATION:

Light Source: LED – available in White only
 Quantity HB LED's: 1
 LED Lens: 23° FWHM Standard
 32° FWHM Optional
 56° FWHM Optional
 LED Life: up to 100,000 hours*.
 *Contact us for LED life information



**SERIES
CON**

FEATURES:

- Built-in Driver
- Aluminum Single Interface Housing
- Auto Burst – LED high current for 500µs ±10% (burst pulse width repeatability ±1% same light), then drops to standard current
- Auto Burst Disable Switch
- 0-10VDC Intensity Control
- Potentiometer Intensity Control
- PWM Dimming Capable (with Auto Burst disabled)
- Internal Thermal Protection
- Robot Friendly Weight – 3.88 oz (110g)

PART NUMBER DESIGNATION: XS40-XXX

XXX = Light Color – WHI, WWH, and NWH

Color	Dash #	Correlated Color Temperature (CCT)	Typ Color Rendering Index (CRI)	Standard Lumen per LED (min)	Burst Lumen per LED (min)
Pure White	-WHI	5000 - 8300K	65	504	1184
Natural White	-NWH	3700 - 5000K	75	468	1100
Warm White	-WWH	2600 - 3700K	80	396	931

Vertrieb durch:

Polytec GmbH
 Polytec Platz 1-7
 D-76337 Waldbronn

Tel: +49(0)7243 / 604-180
 Fax: +49(0)7243 / 69944
 E-Mail: bv@polytec.de
www.polytec.de/bv

