

EL150 LIGHT


EL Series with Internal Driver

ELECTRICAL:

Input Voltage: 23.5-26.4VDC (24VDC \pm 10% burst disabled)
 Input Current: 200 to 350mA typical (1.5A max for burst) @24VDC
Note: Power supply must be capable of 1.5A per light for burst feature to work correctly with supplied cable.
 Strobe Input Impedance: 10K Ω – PNP typical, 9.1K Ω – NPN typical
 Strobe Timing: <20 microseconds from strobe to LED on
 0-10V Input Impedance: 15K Ω typical
 0-10V Input Control: 0V = 100%, 10V = 0% LED current. (Can be left disconnected for 100% LED current)
 Variable Intensity: Adjustable via trim potentiometer from 0% (CCW) to 100% (CW).
 Over-temperature LED: 65 \pm 5°C strobe disable / "Error" LED on; 5°C hyst. for strobe enable / "Error" LED off

Wiring:

| Pin # | Wire Color | Function |
|-------|----------------------|--|
| 1 | Brown | +23.5 to +26.4VDC |
| 2 | White | NPN STROBE INPUT: GND for "ON", Open or >Vin-1V for "OFF" |
| 3 | Blue | 0VDC (DC GND) |
| 4 | Black | PNP STROBE INPUT: < 1 VDC for "OFF", >3 \leq 30 VDC for "ON" |
| 5 | Grey or Green/Yellow | 0-10VDC analog intensity control – 0V = 100%, 10V = 0% |



ENVIRONMENTAL:

Operating Temperature: 0 to 50°C
 Relative Humidity: 5 to 85% non-condensing

MECHANICAL:

Lighted Area: 150mm
 Connector: M12 - 5 pin
 Weight: 8 oz (227g)

ILLUMINATION:

Light Source: LED – available in 4 Colors and IR
 Quantity HB LED's: 5
 LED Lens: 16° FWHM Standard
 23° FWHM Optional
 39° FWHM Optional
 44x15° FWHM Line Optional
 LED Life: up to 50,000 hours*.

*Contact us for LED life information

FEATURES:

- Built-in Driver
- Aluminum Single Interface Housing
- Auto Burst – LED high current for 500 μ s \pm 10%, then drops to standard current
- Auto Burst Disable Switch
- 0-10VDC Intensity Control
- Potentiometer Intensity Control
- PWM Dimming Capable (with Auto Burst disabled)
- Internal Thermal Protection
- Robot Friendly Weight – 8 oz (227g)

PART NUMBER DESIGNATION: EL150-XXX

XXX = Light Color - 470, 530, 630, 850, WHI

| Color | Dash # | λ Dominant Typical | λ Dominant Range | Spectral Half-width $\Delta\lambda_{1/2}$ | λ Peak Typical | Units | Typical mW per LED |
|------------|--------|------------------------------------|--------------------------|---|------------------------|-------|--------------------|
| Blue | -470 | 465 | 455 - 475 | 21 | 453 | nm | 420 |
| Green | -530 | 530 | 525 - 535 | 39 | 518 | nm | 175 |
| Red | -630 | 625 | 618 - 630 | 17 | 632 | nm | 200 |
| Infrared | -850 | 850 | n/a | 30 | 860 | nm | 190 |
| Pure White | -WHI | Color Temp 5700 - 7000K CRI 70 typ | | | | | 360 |

Other colors available on request



Rev. Date: 2013-04-11