



# SPECIFICATION SHEET

# Y

## Model: 7-S2

### KEY FEATURES

Max FPS @ Max Res	7500 fps @ 1920 x 1080
Plus Mode	N/A
Max Frame Rate	85,100 @ 112x64
Minimum Exposure Time	1 $\mu$ s
Sensitivity ASA	6000 ISO Mono 2000 ISO Color
Power Requirements	minimum 12V , 2 A
Operating Temperature	-40+50 °C / -40+122 °F
Memory Options	Internal RAM 8GB / 16GB / 32GB / 64GB
Quantum Efficiency	50%

### SENSOR

Sensor Type	CMOS - Proprietary
Sensor Size	13.9 x 13.9 mm
Sensor Format	1 inch
Image Size	2.0 megapixel
Pixel Size (micron)	7.24x7.24 $\mu$ m
Pixel Depth	10 bit mono 30 bit color

### INPUTS

Trigger	TTL & Switch/Circular buffer with on-camera or software trigger
Sync	Phase-lock TTL
IRIG	Optional
GPS Time Code	Optional
WiFi	Optional

### OUTPUTS

Sync	Frame sync / Strobe
HDMI	30 fps
Comp Video	N/A



### FEATURES

Approx. Size	90.50x90.50x22.00 mm or 3.5x3.5x8.6 inch
Approx. Weight	3.4 kg or 7.5 lbs
Shock/Vibration rating	Shock: 100G / Vibration: 40G - All axes
Battery Powered Operation Time	Operation and battery back-up up to 1 hours
Mount	C-Mount standard , F&PL Adaptor optional

### SOFTWARE

Motion Studio	Windows 32/64 - MAC OS X
Motion Inspector	
Plug-ins/SDK	SDK, LabVIEW™ or MatLab
File Formats	Proprietary RAW (MRF,MCF)
On-the-fly Conversion	TIF,BMP,JPG,PNG,AVI,MPG,TP2,MOV

### COMMUNICATION

Camera Link	N/A
Ethernet	100/1000BaseT
USB 2.0	Standard
WiFi	

Specifications are subject to change without notification.

Data accurate as of 07 May 2013

Please reference our website for updates: <http://www.idtvision.com>



# SPECIFICATION SHEET

# Y

## Model: 7-S1

### KEY FEATURES

Max FPS @ Max Res	5000 fps @ 1920 x 1080
Plus Mode	N/A
Max Frame Rate	32,000 fps @ 1280 x 16
Minimum Exposure Time	1 $\mu$ s
Sensitivity ASA	6000 ISO Mono 2000 ISO Color
Power Requirements	minimum 12V , 2 A
Operating Temperature	-40+50 °C / -40+122 °F
Memory Options	Internal RAM 8GB / 16GB / 32GB / 64GB
Quantum Efficiency	50%

### SENSOR

Sensor Type	CMOS - Proprietary
Sensor Size	13.9 x 13.9 mm
Sensor Format	1 inch
Image Size	2.0 megapixels
Pixel Size (micron)	7.24x7.24 $\mu$ m
Pixel Depth	10 bit mono 30 bit color

### INPUTS

Trigger	TTL & Switch/Circular buffer with on-camera or software trigger
Sync	Phase-lock TTL
IRIG	Optional
GPS Time Code	Optional
WiFi	Optional

### OUTPUTS

Sync	Frame sync / Strobe
HDMI	30 fps
Comp Video	N/A



### FEATURES

Approx. Size	90.50x90.50x22.00 mm or 3.5x3.5x8.6 inch
Approx. Weight	3.4 kg or 7.5 lbs
Shock/Vibration rating	Shock: 100G / Vibration: 40G - All axes
Battery Powered Operation Time	Operation and battery back-up up to 1 hours
Mount	C-Mount standard , F&PL Adaptor optional

### SOFTWARE

Motion Studio	Windows 32/64 - MAC OS X
Motion Inspector	
Plug-ins/SDK	SDK, LabVIEW™ or MatLab
File Formats	Proprietary RAW (MRF,MCF)
On-the-fly Conversion	TIF,BMP,JPG,PNG,AVI,MPG,TP2,MOV

### COMMUNICATION

Camera Link	N/A
Ethernet	100/1000BaseT
USB 2.0	Standard
WiFi	

Specifications are subject to change without notification.

Data accurate as of 07 May 2013

Please reference our website for updates: <http://www.idtvision.com>



# SPECIFICATION SHEET

# Y

## Model: 5-HDiablo

### KEY FEATURES

Max FPS @ Max Res	640 fps @ 2560 x 1920 1020 fps @ 1920 x 1080
Plus Mode	
Max Frame Rate	640 fps @ 2560 x 1920
Minimum Exposure Time	1µs
Sensitivity ASA	3000 ISO Mono 1000 ISO Color
Power Requirements	minimum 12V , 6.5 A
Operating Temperature	0+50 °C/32+122 °F
Memory Options	Internal RAM 8GB / 16GB / 32GB / 64GB
Quantum Efficiency	50%

### SENSOR

Sensor Type	CMOS - Proprietary
Sensor Size	16.0 x 12.1 mm
Sensor Format	1 inch
Image Size	5.0 megapixels
Pixel Size (micron)	7x7 µm
Pixel Depth	10 bit mono 30 bit color

### INPUTS

Trigger	TTL & Switch/Circular buffer with on-camera, remote, or software trigger
Sync	Phase-lock TTL
IRIG	Optional
GPS Time Code	Optional
WiFi	Optional

### OUTPUTS

Sync	Frame sync / Strobe
HDMI	24 fps
Comp Video	N/A



### FEATURES

Approx. Size	90.5 x 90.5 x 220 mm or 3.5 x 3.5 x 8.6 inch
Approx. Weight	3.4 kg or 7.5 lbs
Shock/Vibration rating	Shock: 100G / Vibration: 40G - All axes
Battery Powered Operation Time	Operation with optional battery back-up up to 1 hour
Mount	C-Mount standard , F&PL Adaptor optional

### SOFTWARE

Motion Studio	Windows 32/64 Mac to be released
Motion Inspector	
Plug-ins/SDK	SDK, LabVIEW™ or MatLab
File Formats	Proprietary RAW (MRF,MCF)
On-the-fly Conversion	TIF,BMP,JPG,PNG,AVI,MPG,QT H.264

### COMMUNICATION

Camera Link	N/A
Ethernet	100/1000BaseT
USB 2.0	Standard
WiFi	

Specifications are subject to change without notification.

Data accurate as of 07 May 2013

Please reference our website for updates: <http://www.idtvision.com>



# SPECIFICATION SHEET

# Y

## Model: 5

### KEY FEATURES

Max FPS @ Max Res	730 fps @ 2336 x 1728
Plus Mode	1455 fps @ 2336 x 1728
Max Frame Rate	69,000 fps @ 2336 x 16
Minimum Exposure Time	1 $\mu$ s
Sensitivity ASA	3000 ISO Mono 1000 ISO Color
Power Requirements	minimum 12V , 6.5 A
Operating Temperature	-40°C — +50 °C / -40°F — +122 °F
Memory Options	Internal RAM 8GB / 16GB / 32GB / 64GB
Quantum Efficiency	50%

### SENSOR

Sensor Type	CMOS - Proprietary
Sensor Size	16.0 x 12.1 mm
Sensor Format	1 inch
Image Size	4.0 megapixels
Pixel Size (micron)	7x7 $\mu$ m
Pixel Depth	10 bit mono 30 bit color

### INPUTS

Trigger	TTL & Switch/Circular buffer with on-camera, remote, or software trigger
Sync	Phase-lock TTL
IRIG	Optional
GPS Time Code	Optional
WiFi	Optional

### OUTPUTS

Sync	Frame sync / Strobe
HDMI	24 fps
Comp Video	N/A



### FEATURES

Approx. Size	90.5x90.5x220 mm or 3.5x3.5x8.6 inch
Approx. Weight	3.4 kg or 7.5 lbs
Shock/Vibration rating	Shock: 100G / Vibration: 40G - All axes
Battery Powered Operation Time	Operation with optional battery back-up up to 1 hour
Mount	C-Mount standard , F&PL Adaptor optional

### SOFTWARE

Motion Studio	Windows 32/64 Mac to be released
Motion Inspector	
Plug-ins/SDK	SDK, LabVIEW™ or MatLab
File Formats	Proprietary RAW (MRF,MCF)
On-the-fly Conversion	TIF,BMP,JPG,PNG,AVI,MPG,TP2,QT H.264

### COMMUNICATION

Camera Link	N/A
Ethernet	100/1000BaseT
USB 2.0	Standard
WiFi	

Specifications are subject to change without notification.

Data accurate as of 07 May 2013

Please reference our website for updates: <http://www.idtvision.com>



# SPECIFICATION SHEET

# Y

## Model: 4-S3

### KEY FEATURES

Max FPS @ Max Res	6000 fps @ 1024 x 1024
Plus Mode	11800 fps @ 1024 x 1024
Max Frame Rate	230,000 fps @ 1024 x 16
Minimum Exposure Time	1 $\mu$ s
Sensitivity ASA	6000 ISO Mono 2000 ISO Color
Power Requirements	minimum 12V , 2 A
Operating Temperature	-40°C — +50 °C / -40°F — +122 °F
Memory Options	Internal RAM 8GB / 16GB / 24GB / 32GB
Quantum Efficiency	60%

### SENSOR

Sensor Type	CMOS - Proprietary
Sensor Size	13.9 x 13.9 mm
Sensor Format	1 inch
Image Size	1.0 megapixel
Pixel Size (micron)	13.68x13.68 $\mu$ m
Pixel Depth	10 bit mono 30 bit color

### INPUTS

Trigger	TTL & Switch/Circular buffer with on-camera or software trigger
Sync	Phase-lock TTL
IRIG	Optional
GPS Time Code	Optional
WiFi	Optional

### OUTPUTS

Sync	Frame sync / Strobe
HDMI	30 fps
Comp Video	N/A



### FEATURES

Approx. Size	90.50x90.50x22.00 mm or 3.5x3.5x8.6 inch
Approx. Weight	3.4 kg or 7.5 lbs
Shock/Vibration rating	Shock: 200G / Vibration: 40G - All axes
Battery Powered Operation Time	Operation with optional battery back-up up to 1 hour
Mount	C-Mount standard , F&PL Adaptor optional

### SOFTWARE

Motion Studio	Windows 32/64 MAC OS X - Apple iOS
Motion Inspector	Windows 32 MAC OS X
Plug-ins/SDK	SDK, LabVIEW™ or MatLab
File Formats	Proprietary RAW (MRF,MCF)
On-the-fly Conversion	TIF,BMP,JPG,PNG,AVI,MPG,TP2,MOV

### COMMUNICATION

Camera Link	N/A
Ethernet	100/1000BaseT
USB 2.0	Standard
WiFi	Optional

Specifications are subject to change without notification.

Data accurate as of 07 May 2013

Please reference our website for updates: <http://www.idtvision.com>



# SPECIFICATION SHEET

# Y

## Model: 4-S2

### KEY FEATURES

Max FPS @ Max Res	4500 fps @ 1024 x 1024
Plus Mode	9000 fps @ 1024 x 1024
Max Frame Rate	108,000 fps @ 1024 x 16
Minimum Exposure Time	1 $\mu$ s
Sensitivity ASA	6000 ISO Mono 2000 ISO Color
Power Requirements	minimum 12V , 6.5 A
Operating Temperature	-40°C — +50 °C / -40°F — +122 °F
Memory Options	Internal RAM 8GB / 16GB / 32GB / 64GB
Quantum Efficiency	60%

### SENSOR

Sensor Type	CMOS - Proprietary
Sensor Size	13.9 x 13.9 mm
Sensor Format	1 inch
Image Size	1.0 megapixel
Pixel Size (micron)	13.68x13.68 $\mu$ m
Pixel Depth	10 bit mono 30 bit color

### INPUTS

Trigger	TTL & Switch/Circular buffer with on-camera, remote, or software trigger
Sync	Phase-lock TTL
IRIG	Optional
GPS Time Code	Optional
WiFi	Optional

### OUTPUTS

Sync	Frame sync / Strobe
HDMI	30 fps
Comp Video	N/A



### FEATURES

Approx. Size	90.5x90.5x220 mm or 3.5x3.5x8.6 inch
Approx. Weight	3.4 kg or 7.5 lbs
Shock/Vibration rating	Shock: 100G / Vibration: 40G - All axes
Battery Powered Operation Time	Operation and battery back-up up to 2 hours
Mount	C-Mount standard , F&PL Adaptor optional

### SOFTWARE

Motion Studio	Windows 32/64 Mac to be released
Motion Inspector	Windows 32 MAC OS X
Plug-ins/SDK	SDK, LabVIEW™ or MatLab
File Formats	Proprietary RAW (MRF,MCF)
On-the-fly Conversion	TIF,BMP,JPG,PNG,AVI,MPG,TP2,QT H.264

### COMMUNICATION

Camera Link	N/A
Ethernet	100/1000BaseT
USB 2.0	Standard
WiFi	Optional

Specifications are subject to change without notification.

Data accurate as of 07 May 2013

Please reference our website for updates: <http://www.idtvision.com>



# SPECIFICATION SHEET

# Y

## Model: 4-S1

### KEY FEATURES

Max FPS @ Max Res	3000 fps @ 1024 x 1024
Plus Mode	6000 fps @ 1024 x 1024
Max Frame Rate	72,000 fps @ 1024 x 16
Minimum Exposure Time	1 $\mu$ s
Sensitivity ASA	6000 ISO Mono 2000 ISO Color
Power Requirements	minimum 12V , 6.5 A
Operating Temperature	-40°C — +50 °C / -40°F — +122 °F
Memory Options	Internal RAM 8GB / 16GB / 32GB / 64GB
Quantum Efficiency	60%

### SENSOR

Sensor Type	CMOS - Proprietary
Sensor Size	13.9 x 13.9 mm
Sensor Format	1 inch
Image Size	1.0 megapixel
Pixel Size (micron)	13.68x13.68 $\mu$ m
Pixel Depth	10 bit mono 30 bit color

### INPUTS

Trigger	TTL & Switch/Circular buffer with on-camera, remote, or software trigger
Sync	Phase-lock TTL
IRIG	Optional
GPS Time Code	Optional
WiFi	Optional

### OUTPUTS

Sync	Frame sync / Strobe
HDMI	30 fps
Comp Video	N/A



### FEATURES

Approx. Size	90.5x90.5x220 mm or 3.5x3.5x8.6 inch
Approx. Weight	3.4 kg or 7.5 lbs
Shock/Vibration rating	Shock: 100G / Vibration: 40G - All axes
Battery Powered Operation Time	Operation with optional battery back-up up to 1 hour
Mount	C-Mount standard , F&PL Adaptor optional

### SOFTWARE

Motion Studio	Windows 32/64 Mac to be released
Motion Inspector	Windows 32 MAC OS X
Plug-ins/SDK	SDK, LabVIEW™ or MatLab
File Formats	Proprietary RAW (MRF,MCF)
On-the-fly Conversion	TIF,BMP,JPG,PNG,AVI,MPG,TP2,QT H.264

### COMMUNICATION

Camera Link	N/A
Ethernet	100/1000BaseT
USB 2.0	Standard
WiFi	Optional

Specifications are subject to change without notification.

Data accurate as of 07 May 2013

Please reference our website for updates: <http://www.idtvision.com>



# SPECIFICATION SHEET

# Y

## Model: 3-S2

### KEY FEATURES

Max FPS @ Max Res	6000 fps @ 1280 x 1024
Plus Mode	N/A
Max Frame Rate	>140,000 fps @ 1280 x 16
Minimum Exposure Time	1 $\mu$ s
Sensitivity ASA	6000 ISO Mono 2000 ISO Color
Power Requirements	minimum 12V , 6.5 A
Operating Temperature	-40°C — +50 °C / -40°F — +122 °F
Memory Options	Internal RAM 8GB / 16GB / 32GB / 64GB
Quantum Efficiency	60%

### SENSOR

Sensor Type	CMOS - Proprietary
Sensor Size	13.9 x 13.9 mm
Sensor Format	1 inch
Image Size	1.3 megapixel
Pixel Size (micron)	Effective 10.94x10.94 $\mu$ m
Pixel Depth	10 bit mono 30 bit color

### INPUTS

Trigger	TTL & Switch/Circular buffer with on-camera, remote, or software trigger
Sync	Phase-lock TTL
IRIG	Optional
GPS Time Code	Optional
WiFi	Optional

### OUTPUTS

Sync	Frame sync / Strobe
HDMI	30 fps
Comp Video	N/A



### FEATURES

Approx. Size	90.5x90.5x220 mm or 3.5x3.5x8.6 inch
Approx. Weight	3.4 kg or 7.5 lbs
Shock/Vibration rating	Shock: 100G / Vibration: 40G - All axes
Battery Powered Operation Time	Operation with optional battery back-up up to 1 hour
Mount	C-Mount standard , F&PL Adaptor optional

### SOFTWARE

Motion Studio	Windows 32/64 Mac to be released
Motion Inspector	
Plug-ins/SDK	SDK, LabVIEW™ or MatLab
File Formats	Proprietary RAW (MRF,MCF)
On-the-fly Conversion	TIF,BMP,JPG,PNG,AVI,MPG,QT H.264

### COMMUNICATION

Camera Link	N/A
Ethernet	100/1000BaseT
USB 2.0	Standard
WiFi	

Specifications are subject to change without notification.

Data accurate as of 07 May 2013

Please reference our website for updates: <http://www.idtvision.com>



# SPECIFICATION SHEET

# Y

## Model: 3-S1

### KEY FEATURES

Max FPS @ Max Res	3750 fps @ 1280 x 1024
Plus Mode	N/A
Max Frame Rate	88,000 fps @ 1280 x 16
Minimum Exposure Time	1µs
Sensitivity ASA	6000 ISO Mono 2000 ISO Color
Power Requirements	minimum 12V , 2 A
Operating Temperature	-40°C — +50 °C / -40°F — +122 °F
Memory Options	Internal RAM 8GB / 16GB / 24GB / 32GB
Quantum Efficiency	60%

### SENSOR

Sensor Type	CMOS - Proprietary
Sensor Size	13.9 x 12.3 mm
Sensor Format	1 inch
Image Size	1.3 megapixels
Pixel Size (micron)	Effective 10.85x10.85 µm
Pixel Depth	10 bit mono 30 bit color

### INPUTS

Trigger	TTL & Switch/Circular buffer with on-camera or software trigger
Sync	Phase-lock TTL
IRIG	Optional
GPS Time Code	Optional
YiFi	Optional

### OUTPUTS

Sync	Frame sync / Strobe
HDMI	30 fps
Comp Video	N/A



### FEATURES

Approx. Size	90.50x90.50x22.00 mm or 3.5x3.5x8.6 inch
Approx. Weight	3.4 kg or 7.5 lbs
Shock/Vibration rating	Shock: 200G / Vibration: 40G - All axes
Battery Powered Operation Time	Operation with optional battery back-up up to 1 hour
Mount	C-Mount standard , F&PL Adaptor optional

### SOFTWARE

Motion Studio	Windows 32/64 - MAC OS X - Apple iOS
Motion Inspector	
Plug-ins/SDK	SDK, LabVIEW™ or MatLab
File Formats	Proprietary RAW (MRF,MCF)
On-the-fly Conversion	TIF,BMP,JPG,PNG,AVI,MPG,TP2,MOV

### COMMUNICATION

Camera Link	N/A
Ethernet	100/1000BaseT
USB 2.0	Standard
WiFi	

Specifications are subject to change without notification.

Data accurate as of 07 May 2013

Please reference our website for updates: <http://www.idtvision.com>



# Y

## Model: 3-HDiablo

### KEY FEATURES

Max FPS @ Max Res	1470 fps @ 1920 x 1080
Plus Mode	N/A
Max Frame Rate	1400 fps @ 1920 x 1080
Minimum Exposure Time	1 $\mu$ s
Sensitivity ASA	3000 ISO Mono 1000 ISO Color
Power Requirements	minimum 12V , 6.5 A
Operating Temperature	0+50 °C/32+122 °F
Memory Options	Internal RAM 8GB / 16GB / 32GB / 64GB
Quantum Efficiency	40%



### SENSOR

Sensor Type	CMOS - Proprietary
Sensor Size	15.4 x 12.3 mm
Sensor Format	1 inch
Image Size	2.0 megapixel
Pixel Size (micron)	12x12 $\mu$ m
Pixel Depth	10 bit mono 30 bit color

### INPUTS

Trigger	TTL & Switch/Circular buffer with oncamera, remote, or software trigger
Sync	Phase-lock TTL
IRIG	N/A
GPS Time Code	N/A
WiFi	Optional

### OUTPUTS

Sync	Frame sync / Strobe
HDMI	30 fps
Comp Video	N/A

### FEATURES

Approx. Size	90.5x90.5x220 mm or 3.5x3.5x8.6 inch
Approx. Weight	3.4 kg or 7.5 lbs
Shock/Vibration rating	Shock: 100G / Vibration: 40G - All axes
Battery Powered Operation Time	Operation with optional battery back-up up to 1 hour
Mount	C-Mount standard , F&PL Adaptor optional

### SOFTWARE

Motion Studio	Windows 32/64 Mac to be released
Motion Inspector	
Plug-ins/SDK	SDK, LabVIEW™ or MatLab
File Formats	Proprietary RAW (MRF,MCF)
On-the-fly Conversion	TIF,BMP,JPG,PNG,AVI,MPG,TP2,QT H.264

### COMMUNICATION

Camera Link	N/A
Ethernet	100/1000BaseT
USB 2.0	Standard
WiFi	

Specifications are subject to change without notification.

Data accurate as of 07 May 2013

Please reference our website for updates: <http://www.idtvision.com>



Y

# Model: 3-Classic

## KEY FEATURES

Max FPS @ Max Res	1000 fps @ 1280 x 1024
Plus Mode	2000 fps @ 1280 x 1024
Max Frame Rate	62,000 fps @ 1280 x 16
Minimum Exposure Time	1 $\mu$ s
Sensitivity ASA	3000 ISO Mono 1000 ISO Color
Power Requirements	minimum 12V , 6.5 A
Operating Temperature	-40°C — +50 °C / -40°F — +122 °F
Memory Options	Internal RAM 8GB / 16GB / 32GB / 64GB
Quantum Efficiency	40%

## SENSOR

Sensor Type	CMOS - Proprietary
Sensor Size	15.4 x 12.3 mm
Sensor Format	1 inch
Image Size	1.3 megapixel
Pixel Size (micron)	12x12 $\mu$ m
Pixel Depth	10 bit mono 30 bit color

## INPUTS

Trigger	TTL & Switch/Circular buffer with on-camera, remote, or software trigger
Sync	Phase-lock TTL
IRIG	Optional
GPS Time Code	Optional
WiFi	Optional

## OUTPUTS

Sync	Frame sync / Strobe
HDMI	30 fps
Comp Video	N/A



## FEATURES

Approx. Size	90.5x90.5x220 mm or 3.5x3.5x8.6 inch
Approx. Weight	3.4 kg or 7.5 lbs
Shock/Vibration rating	Shock: 100G / Vibration: 40G - All axes
Battery Powered Operation Time	Operation with optional battery back-up up to 1 hour
Mount	C-Mount standard , F&PL Adaptor optional

## SOFTWARE

Motion Studio	Windows 32/64 Mac to be released
Motion Inspector	
Plug-ins/SDK	SDK, LabVIEW™ or MatLab
File Formats	Proprietary RAW (MRF,MCF)
On-the-fly Conversion	TIF,BMP,JPG,PNG,AVI,MPG,TP2,QT H.264

## COMMUNICATION

Camera Link	N/A
Ethernet	100/1000BaseT
USB 2.0	Standard
WiFi	

Specifications are subject to change without notification.

Data accurate as of 07 May 2013

Please reference our website for updates: <http://www.idtvision.com>



# SPECIFICATION SHEET

# Y

## Model: 7-S3

### KEY FEATURES

Max FPS @ Max Res	9000 fps @ 1920 x 1080
Plus Mode	N/A
Max Frame Rate	110,000 @ 112x64
Minimum Exposure Time	1 $\mu$ s
Sensitivity ASA	6000 ISO Mono 2000 ISO Color
Power Requirements	minimum 12V , 2 A
Operating Temperature	-40+50 °C / -40+122 °F
Memory Options	Internal RAM 8GB / 16GB / 32GB / 64GB
Quantum Efficiency	50%

### SENSOR

Sensor Type	CMOS - Proprietary
Sensor Size	13.9 x 13.9 mm
Sensor Format	1 inch
Image Size	2.0 megapixel
Pixel Size (micron)	7.24x7.24 $\mu$ m
Pixel Depth	10 bit mono 30 bit color

### INPUTS

Trigger	TTL & Switch/Circular buffer with on-camera or software trigger
Sync	Phase-lock TTL
IRIG	Optional
GPS Time Code	Optional
WiFi	Optional

### OUTPUTS

Sync	Frame sync / Strobe
HDMI	30 fps
Comp Video	N/A



### FEATURES

Approx. Size	90.50x90.50x22.00 mm or 3.5x3.5x8.6 inch
Approx. Weight	3.4 kg or 7.5 lbs
Shock/Vibration rating	Shock: 100G / Vibration: 40G - All axes
Battery Powered Operation Time	Operation and battery back-up up to 1 hours
Mount	C-Mount standard , F&PL Adaptor optional

### SOFTWARE

Motion Studio	Windows 32/64 - MAC OS X
Motion Inspector	
Plug-ins/SDK	SDK, LabVIEW™ or MatLab
File Formats	Proprietary RAW (MRF,MCF)
On-the-fly Conversion	TIF,BMP,JPG,PNG,AVI,MPG,TP2,MOV

### COMMUNICATION

Camera Link	N/A
Ethernet	100/1000BaseT
USB 2.0	Standard
WiFi	

Specifications are subject to change without notification.

Data accurate as of 07 May 2013

Please reference our website for updates: <http://www.idtvision.com>